



Model:  
**B-510-2**

Typology:  
**ROUTINE MICROSCOPE**

**Description:**  
*Laboratory microscope for routine and research applications. Dye-cast frame, with high stability and ergonomy, for transmitted light observation.*

<b>Illumination</b>	<p>Light source: X-LED<sup>3</sup>, light intensity control using a knob on left side of the frame. LED power: 3.6 W, comparable to a 50 W halogen bulb. Color temperature: 6,300 K. LED lifetime: &gt; 65,000 hours.</p> <p>Power supply: Input 110/240 Vac, 50/60 Hz; Output 6 Vdc 2.5 A. Max. required power: 6 W.</p> <p>Köhler illumination system with Field Diaphragm.</p>
<b>Observation Modes</b>	Brightfield.
<b>Focusing</b>	<p>Coaxial coarse and fine focusing mechanism (graduated, 0.002 mm) with upper stop, to prevent the contact between objective and specimen. Flat fine focusing knob on the right side. Adjustable tension of coarse focusing knob.</p>
<b>Stage</b>	Double layer with mechanical sliding stage, size 233x147 mm, X-Y movement range 78x54 mm. Belt-drive in X direction. Vernier scale on two axes, accuracy 0.1 mm.
<b>Nosepiece</b>	Quintuple revolving nosepiece, rotation on ball bearings.
<b>Head</b>	<p>Trinocular observation head, inclined 30° and rotatable 360° Diopter adjustment on left eyepiece (+- 5 diopter adjustment). Interpupillary adjustment 50 - 75 mm. Fixed photo port, 50/50 ratio. Multi-viewing device (1 observer simultaneous with the main observer). <b>Discussion LED pointer with 3 selectable colors (red, green, blue) and intensity adjustment.</b></p>
<b>Eyepieces</b>	<p>Plan Extra Wide Field, PL 10x/22, High Eyepoint (on main head). Wide Field, WF 10x/20, High Eyepoint (on discussion head).</p>
<b>Objectives</b>	<p>Infinity corrected optical system IOS. - IOS W-PLAN 4x/0.10, W.D. 17.3 mm - IOS W-PLAN 10x/0.25, W.D. 10 mm - IOS W-PLAN 40x/0.65, W.D. 0.54 mm - IOS W-PLAN 100x/1.25, W.D. 0.13 mm (oil immersion) All objectives have anti-fungus treatment.</p>
<b>Condenser</b>	Swing-out type condenser, sliding-in, N.A. 0.2/0.9, with centering system.
<b>Dimensions</b>	<p>HEIGHT: 480 mm WIDTH: 815 mm DEPTH: 410 mm WEIGHT: 14 kg</p>
<b>Accessories</b>	Instruction manual and dust cover included.

BYk 'Mcf\_ A]WcgVdY7 ca dUmi-bW  
FECSæ { a] Sca ^EU' a' /OFA a' çal^Ea^, Ä[ \ \AFi €  
V\BAi iEi iE Gi ÄZca KAFi E €FGE i  
, , , E a[ •& ] ^ã c!) aã } aB { ÄZa } O} ^•& ] ^•B {