



# STEINDORFF®

## Stereo Microscope

### NYMCS-310 & NYMCS-311

## Operation Manual



It is recommended strongly that you study this manual thoroughly before using the microscope. Retain this manual in an easily accessible place near the work desk for future reference.

**NEW YORK MICROSCOPE COMPANY INC.**  
AKA MEL SOBEL MICROSCOPES

---


100A Lauman Ln., Hicksville, N.Y. 11801 Toll Free: (877) 877-7274 • Fax: (516) 801-2046  
Web Site: [www.microscopeinternational.com](http://www.microscopeinternational.com) • [www.nyscopes.com](http://www.nyscopes.com) • E-mail: [Info@nyscopes.com](mailto:Info@nyscopes.com)



# STEINDORFF®

## 1. DESCRIPTION

NYMCS-310/311 Stereo microscopes are with fully coated with excellent optical system, high resolution and crisp erect image. They are widely used in electric factories, schools laboratories, sculpture and families, etc.



- |                                |                      |
|--------------------------------|----------------------|
| 1. WF10X Eyepiece              | 7. Focusing Knob     |
| 2. Eyepiece Diopter Adjustment | 8. Fastening Knob    |
| 3. Prism Housing               | 9. Transmitted Light |
| 4. Objective Cover             | 10. Power Switch     |
| 5. Stage Clips                 | 11. Incident Light   |
| 6. Stage                       |                      |

# STEINDORFF®

## 2. TECHNOLOGY DATA

Power Supply	220V/50HZ (110V/50Hz or 110V/60Hz is optional)
Illuminator	12V 10W-tungsten lamp
Interpupillary Distance Adjustment	55mm-75mm
Diopter Adjustment	+5dp
Magnification	20X, 40X

## 3. OPERATION DESCRIPTION

- A. Set the microscope on a lever table.
- B. Place the specimen on the center of the stage (6). If need, keep the specimen under the stage clips (5) to fix the objective.
- C. Loosen the fastening knob (8) and move the head up or down until the specimen within the working distance, then tighten the fastening knob.
- D. Observe through the right eyepiece (1) and slowly dual operates the focusing knob (7) to get a clear image. Then observe the left eyepiece (1), if the image is not clear, you should adjust the diopter (2) to get a clear one.
- E. Rotating prism housing (3) to suit your interpupillary distance to obtain a crisp stereo image. Rotate the objective cover (4) to choose the 20X or 40X magnification.

**Notice:** Shut off the power supply when replace the bulb.

Objective must be within the working distance when using.

Turn off power switch when not in use.

## 4. OPERATION DESCRIPTION

Put the microscope in cool and dry place.

Cover it with the plastic dust cover when not in use. Check up and regularly grease the movable parts.

All the optic are adjusted and could take apart by yourself. When the lens and other optical parts covered with dust, you should wipe with volatile solvents or abrasive cleaners. Never wipe the surface of any optical with your hands.

Deliver to a professional shop for repair when not in use.

**NEW YORK MICROSCOPE COMPANY INC.**  
AKA MEL SOBEL MICROSCOPES

100A Lauman Ln., Hicksville, N.Y. 11801 Toll Free: (877) 877-7274 • Fax: (516) 801-2046  
Web Site: [www.microscopeinternational.com](http://www.microscopeinternational.com) • [www.nyscopes.com](http://www.nyscopes.com) • E-mail: [Info@nyscopes.com](mailto:Info@nyscopes.com)

